

Revision Date: 07/31/2016

Print Date: 11/1/2016 SDS Number: R0172170

Version: 1.1

Valvoline[™] GM MULTIPURPOSE GREASE

VV614

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name

: Valvoline™ GM MULTIPURPOSE GREASE

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet	Emergency telephone number 1-800-VALVOLINE
Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509	Regulatory Information Number 1-800-TEAMVAL
United States of America	Product Information
SDS@valvoline.com	1-800-TEAMVAL

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	Asp. Tox. 1; H304	74.99

Valvoline.	Page: 2
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0172170
Valvoline™ GM MULTIPURPOSE GREASE	Version: 1.1
VV614	

/	ASPHALT	 Not a hazardous substance or mixture.	24.99
ł	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA	Not a hazardous substance or mixture.	9.99

SECTION 4. FIRST AID MEASURES			
General advice	: No	hazards which require special first aid measures.	
If inhaled	lf u adv	preathed in, move person into fresh air. Inconscious place in recovery position and seek medical vice. Symptoms persist, call a physician.	
In case of skin contact	rec	st aid is not normally required. However, it is commended that exposed areas be cleaned by washing h soap and water.	
In case of eye contact		move contact lenses. Dtect unharmed eye.	
If swallowed	Ne	not give milk or alcoholic beverages. ever give anything by mouth to an unconscious person. symptoms persist, call a physician.	
Most important symptoms and effects, both acute and delayed	pro asp lon of r (i.e fibr app per sho occ wo	ute aspiration of large amounts of oil-laden material may oduce a serious aspiration pneumonia. Patients who pirate these oils should be followed for the development of ag-term sequelae. Repeated aspiration of small quantities mineral oil can produce chronic inflammation of the lungs e. lipoid pneumonia) that may progress to pulmonary rosis. Symptoms are often subtle and radiological changes pear worse than clinical abnormalities. Occasionally, rsistent cough, irritation of the upper respiratory tract, ortness of breath with exertion, fever, and bloody sputum cur. Inhalation exposure to oil mists below current rkplace exposure limits is unlikely to cause pulmonary normalities.	
	bre the sto	gns and symptoms of exposure to this material through eathing, swallowing, and/or passage of the material through e skin may include: omach or intestinal upset (nausea, vomiting, diarrhea) tation (nose, throat, airways)	
Notes to physician	: No	hazards which require special first aid measures.	

Valvoline	Page: 3
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0172170
Valvoline™ GM MULTIPURPOSE GREASE	Version: 1.1
VV614	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	carbon dioxide and carbon monoxide sulfur oxides Hydrocarbons Aldehydes Ketones Nitrogen oxides (NOx) Sulphur oxides
Specific extinguishing methods	:	
		Product is compatible with standard fire-fighting agents.
Further information	:	Standard procedure for chemical fires.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions	: Prevent further leakage or spillage if safe to do so.
Methods and materials for containment and cleaning up	 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
Other information	: Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Smoking, eating and drinking should be prohibited in the



Revision Date: 07/31/2016

Print Date: 11/1/2016

SDS Number: R0172170 Version: 1.1

Valvoline™ GM MULTIPURPOSE GREASE

VV614

Materials to avoid

 application area.

 For personal protection see section 8.

 Conditions for safe storage
 : Electrical installations / working materials must comply with the technological safety standards.

:	No materials to be	especially	/ mentioned.
•		oopoolail	, mondonou.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	PEL	500 ppm 2,000 mg/m3	OSHA_TRA NS
		REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRA NS
		TWA	5 mg/m3 Mist.	Z1A
		TWA	400 ppm 1,600 mg/m3	Z1A
ASPHALT	8052-42-4	TWA	0.5 mg/m3 Inhalable fraction. (as benzene solubles)	ACGIH
		Ceil_Time	5 mg/m3 Fume.	NIOSH/GUID E
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA	64742-52-5	PEL	500 ppm 2,000 mg/m3	OSHA_TRA NS
		REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRA NS

Components with workplace control parameters

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known,



Revision Date: 07/31/2016

Print Date: 11/1/2016 SDS Number: R0172170

Version: 1.1

Valvoline™	GM MULTIPURPOSE	GREASE

VV614

suspected or apparent adverse effects.

Personal protective equipment				
Respiratory protection	: No personal respiratory protective equipment normally required.			
Eye protection	: Not required under normal conditions of use. Wear splash- proof safety goggles if material could be misted or splashed into eyes.			
Skin and body protection	 Wear as appropriate: Safety shoes Wear resistant gloves (consult your safety equipment supplier). 			
Hygiene measures	: General industrial hygiene practice.			

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: gel	
Physical state	: liquid	
Colour	: red	
Odour	: No data ava	ilable
Odour Threshold	: No data ava	ilable
рН	: No data ava	ilable
Melting point/freezing point	: No data ava	ilable
	: 640 °F / 338	°C
Flash point	: 471 °F / 244	°C
Evaporation rate	: No data ava	ilable
Flammability (solid, gas)	: No data ava	ilable
Upper explosion limit	: No data ava	ilable
Lower explosion limit	: No data ava	ilable
Vapour pressure	: < 0.01 mmH	lg (20 °C)
Relative vapour density	: No data ava	ilable



Valvoline™ GM MULTIPURPOSE GREASE

VV614

Relative density	: 0.95 (15.6 °C)
Density	: 0.90 g/cm3 (20 °C)
Solubility(ies) Water solubility	: negligible
Solubility in other solvents	: No data available
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: > 315 °C
Thermal decomposition	: No data available
Viscosity Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 20.5 mm2/s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	carbon dioxide and carbon monoxide Hydrocarbons Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of	:	Inhalation
exposure		Skin contact
		Eye Contact



Revision Date: 07/31/2016

Print Date: 11/1/2016

SDS Number: R0172170 Version: 1.1

Valvoline™ GM MULTIPURPOSE GREASE

VV614

Ingestion

Acute toxicity Not classified based on availa	ble information.
Product: Acute oral toxicity	: Acute toxicity estimate (Rat): 3,019 mg/kg
Acute dermal toxicity	: Acute toxicity estimate (Rabbit): 169,492 mg/kg
<u>Components:</u> DISTILLATES (PETROLEUM Acute oral toxicity), SOLVENT-DEWAXED HEAVY PARAFFINIC : : LD 50 (Rat): > 5,000 mg/kg
Acute dermal toxicity	: LD 50 (Rabbit): > 5,000 mg/kg
DISTILLATES (PETROLEUM Acute oral toxicity), HYDROTREATED HEAVY NAPHTA: : LD 50 (Rat): > 5 g/kg
Acute inhalation toxicity	 LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: Not classified as acutely toxic by inhalation under GHS.
Acute dermal toxicity	 LD 50 (Rabbit): > 2,000 mg/kg Assessment: Not classified as acutely toxic by dermal absorption under GHS. Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information. <u>Product:</u> Result: Not irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC: Result: Mildly irritating to skin

ASPHALT: Result: Not irritating to skin

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA: Species: Rabbit Result: Not irritating to skin

Serious eye damage/eye irritation Not classified based on available information. Product:



Version: 1.1

Revision Date: 07/31/2016

Print Date: 11/1/2016 SDS Number: R0172170

Valvoline[™] GM MULTIPURPOSE GREASE

VV614

Result: Not irritating to eyes

Remarks: Unlikely to cause eye irritation or injury.

Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC: Result: Mildly irritating to eyes

ASPHALT: Result: Possibly irritating to eyes

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA: Species: Rabbit Result: Mildly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information. Components: DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA: Species: Guinea pig Assessment: Does not cause skin sensitisation. Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information. **Carcinogenicity** Not classified based on available information. **Reproductive toxicity** Not classified based on available information. **STOT - single exposure** Not classified based on available information. **STOT - repeated exposure** Not classified based on available information. **Aspiration toxicity** Not classified based on available information. **Product:** No aspiration toxicity classification

<u>Components:</u> DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC: May be fatal if swallowed and enters airways.

Further information <u>Product:</u> Remarks: No data available

Carcinogenicity: IARC

Group 2B: Possibly carcinogenic to humans

ASPHALT

8052-42-4

	voline	Page: 9	
SAFETY DATA SH	IEET	Revision Date: 07/31/2016	
		Print Date: 11/1/2016	
		SDS Number: R0172170	
Valvoline [™] GM MULTIPURPOSE GREASE		Version: 1.1	
VV614			
OSHA	equal to 0.1% is i	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:	
	LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203
Toxicity to daphnia and other : aquatic invertebrates	EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae :	NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to daphnia and other : aquatic invertebrates (Chronic toxicity)	NOEL (Daphnia (water flea)): 10 mg/l Exposure time: 21 d Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 211
Persistence and degradability DISTILLATES (PETROLEUM), H	IYDROTREATED HEAVY NAPHTA:
	Result: Inherently biodegradable Biodegradation: 31 % Exposure time: 28 d Method: OECD Test Guideline 301F

Bioaccumulative potential

No data available

Valvoline	Page: 10
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0172170
Valvoline™ GM MULTIPURPOSE GREASE	Version: 1.1
VV614	
Mobility in soil No data available	

Other adverse effects No data available

Product:

Additional ecological information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods		
General advice	:	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

Valvoline	Page: 11
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0172170
Valvoline™ GM MULTIPURPOSE GREASE	Version: 1.1
VV614	

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

: No SARA Hazards
: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
Proposition 65 warnings are not required for this product based on the results of a risk assessment.
ict are reported in the following inventories: : On TSCA Inventory
: On the inventory, or in compliance with the inventory
: All components of this product are on the Canadian DSL.
: On the inventory, or in compliance with the inventory
: On the inventory, or in compliance with the inventory

Valvoline.	Page: 12
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0172170
Valvoline™ GM MULTIPURPOSE GREASE	Version: 1.1
VV614	

PICCS

: On the inventory, or in compliance with the inventory

IECSC

: On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/31/2016



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).



Version: 1.1



Revision Date: 07/31/2016

Print Date: 11/1/2016 SDS Number: R0172170

Valvoline™ GM MULTIPURPOSE GREASE	

VV614

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization" IMDG : International Maritime Code for Dangerous Goods ISO : International Organization for Standardization logPow : octanol-water partition coefficient LCxx : Lethal Concentration, for xx percent of test population LDxx : Lethal Dose, for xx percent of test population. ICxx : Inhibitory Concentration for xx of a substance Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified OECD : Organization for Economic Co-operation and Development **OEL** : Occupational Exposure Limit P-Statement : Precautionary Statement PBT : Persistent, Bioaccumulative and Toxic **PPE : Personal Protective Equipment** STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity TLV : Threshold Limit Value TWA : Time-weighted average vPvB : Very Persistent and Very Bioaccumulative WEL : Workplace Exposure Level CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act DOT : Department of Transportation FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System