

SAFETY DATA SHEET

Creation Date 24-Apr-2009 Revision Date 19-May-2015 Revision Number 3

1. Identification

Product Name Ethanol, 200 proof

Cat No.: AC615090000; AC615090010; AC615090020; AC615090040;

AC615091000; AC615095000

Synonyms Ethyl alcohol; Absolute ethanol

Recommended Use Laboratory chemicals.

Uses advised against No Information available

Details of the supplier of the safety data sheet

Company Entity / Business Name

Fisher Scientific Acros Organics
One Reagent Lane One Reagent Lane

Fair Lawn, NJ 07410 Fair Lawn, NJ 07410 Tel: (201) 796-7100

Emergency Telephone Number

For information US call: 001-800-ACROS-01

/ Europe call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 /

Europe: +32 14 57 52 99

CHEMTREC Tel. No.US:001-800-424-9300 /

Europe:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 2
Serious Eye Damage/Eye Irritation Category 2
Specific target organ toxicity (single exposure) Category 3

Target Organs - Central nervous system (CNS).

Specific target organ toxicity - (repeated exposure) Category 2

Target Organs - Kidney, Liver, Blood.

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor Causes serious eye irritation May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Response

Get medical attention/advice if you feel unwell

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a closed container

Store in a well-ventilated place. Keep cool

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None identified

3. Composition / information on ingredients

Component	CAS-No	Weight %
Ethyl alcohol	64-17-5	99-100

4. First-aid measures

Eye ContactRinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Obtain medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if

symptoms occur.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately if

symptoms occur.

Ingestion Do not induce vomiting. Obtain medical attention.

Most important symptoms/effects Breathing difficulties. . Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like

Ethanol, 200 proof

headache, dizziness, tiredness, nausea and vomiting

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Use water spray to

cool unopened containers. Cool closed containers exposed to fire with water spray.

Unsuitable Extinguishing Media Water may be ineffective, Do not use a solid water stream as it may scatter and spread fire

Flash Point 12 °C / 53.6 °F Method - No information available

Autoignition Temperature

Explosion Limits

363 °C / 685.4 °F

Upper 19 vol % **Lower** 3.3 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO2)

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health	Flammability	Instability	Physical hazards
2	3	0	N/A

Accidental release measures

Personal Precautions Use personal protective equipment. Ensure adequate ventilation. Remove all sources of

ignition. Take precautionary measures against static discharges. Do not get in eyes, on

skin, or on clothing.

Environmental Precautions Should not be released into the environment.

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable,

Up

closed containers for disposal. Take precautionary measures against static discharges. Use

spark-proof tools and explosion-proof equipment.

- 7.	. ト	landl	lina	and	storage
, ,		iai iai	11114	and	J.C. aq

Handling Wear personal protective equipment. Ensure adequate ventilation. Keep away from open

flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing.

Do not ingest. Use spark-proof tools and explosion-proof equipment.

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

open flames, hot surfaces and sources of ignition. Flammables area.

8. Exposure controls / personal protection

Exposure Guidelines

Ethanol, 200 proof

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000 ppm	IDLH: 3300 ppm
		(Vacated) TWA: 1900 mg/m ³	TWA: 1000 ppm
		TWA: 1000 ppm	TWA: 1900 mg/m ³
		TWA: 1900 mg/m ³	

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV		
Ethyl alcohol	TWA: 1000 ppm	TWA: 1000 ppm	STEL: 1000 ppm		
	TWA: 1880 mg/m ³	TWA: 1900 mg/m ³			

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers

are close to the workstation location.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Wear appropriate protective gloves and clothing to prevent skin exposure. Skin and body protection

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

> EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Handle in accordance with good industrial hygiene and safety practice. **Hygiene Measures**

Physical and chemical properties

Physical State Liquid

Appearance Clear, Colorless sweet, Characteristic Odor

Odor Threshold No information available No information available pН

Melting Point/Range -114 °C / -173.2 °F 78 °C / 172.4 °F **Boiling Point/Range** 12 °C / 53.6 °F **Flash Point**

No information available **Evaporation Rate**

Flammability (solid,gas) Not applicable

Flammability or explosive limits Upper 19 vol %

Lower 3.3 vol % **Vapor Pressure** No information available **Vapor Density** No information available **Relative Density** No information available

No information available Solubility Partition coefficient; n-octanol/water No data available **Autoignition Temperature** 363 °C / 685.4 °F

Decomposition Temperature No information available Viscosity No information available

Molecular Formula C2 H6 O **Molecular Weight** 46.07

10. Stability and reactivity

Revision Date 19-May-2015 Ethanol, 200 proof

Reactive Hazard None known, based on information available

Hygroscopic. Stability

Conditions to Avoid Incompatible products. Heat, flames and sparks. Keep away from open flames, hot

surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids, Acid anhydrides, Acid chlorides

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	
Ethyl alcohol	3450 mg/kg (Mouse)	Not listed	20000 ppm/10H (Rat)	

Toxicologically Synergistic

Products

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritating to eyes Irritation

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Ethyl alcohol	64-17-5	Group 1	Not listed	A3	Χ	Not listed
ACCIU, (Amorica	n Conformed of Co	warnmantal Industr	Human Carainagan			

ACGIH: (American Conference of Governmental Industrial

OSHA: (Occupational Safety & Health Administration)

Hygienists)

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

X - Present

Mexico - Occupational Exposure Limits - Carcinogens Mexico - Occupational Exposure Limits - Carcinogens

A1 - Confirmed Human Carcinogen A2 - Suspected Human Carcinogen A3 - Confirmed Animal Carcinogen

A4 - Not Classifiable as a Human Carcinogen A5 - Not Suspected as a Human Carcinogen

Mutagenic Effects Mutagenic effects have occurred in humans.

Adverse reproductive effects have occurred in humans. **Reproductive Effects**

Substances known to cause developmental toxicity in humans. **Developmental Effects**

Teratogenicity Teratogenic effects have occurred in humans.

Central nervous system (CNS) STOT - single exposure

Kidney Liver Blood STOT - repeated exposure

Aspiration hazard Aspiration hazard

delayed

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

•

tiredness, nausea and vomiting

Endocrine Disruptor Information

Ethanol, 200 proof

No information available

Other Adverse Effects Tun

Tumorigenic effects have been reported in experimental animals. See actual entry in

RTECS for complete information.

12. Ecological information

Ecotoxicity

.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl alcohol	EC50 (72h) = 275 mg/l	Fathead minnow	Photobacterium	EC50 = 9268 mg/L/48h
	(Chlorella vulgaris)	(Pimephales promelas)	phosphoreum:EC50 = 34634	EC50 = 10800 mg/L/24h
		LC50 = 14200 mg/l/96h	mg/L/30 min	
			Photobacterium	
			phosphoreum:EC50 = 35470	
			mg/L/5 min	

Persistence and Degradability Bioaccumulation/ Accumulation

Persistence is unlikely based on information available. Soluble in water

No information available.

Mobility

Will likely be mobile in the environment due to its water solubility.

Component	log Pow
Ethyl alcohol	-0.32

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN1170
Proper Shipping Name ETHANOL

Hazard Class 3
Packing Group ||

TDG

UN-No UN1170
Proper Shipping Name ETHANOL

Hazard Class 3
Packing Group ||

IATA

UN-No UN1170
Proper Shipping Name ETHANOL

Hazard Class 3
Packing Group ||

IMDG/IMO UN-No

UN-No UN1170
Proper Shipping Name ETHANOL

Hazard Class 3
Packing Group ||

15. Regulatory information

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Ethyl alcohol	Χ	Χ	1	200-578-6	1		Χ	Χ	Χ	Х	Χ

Legend:

X - Listed

- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313 Not applicable

SARA 311/312 Hazardous Categorization

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

Clean Water Act Not applicable

Clean Air Act Not applicable

OSHA Occupational Safety and Health Administration

Not applicable

CERCLA

Not applicable

California Proposition 65

This product contains the following Proposition 65 chemicals: Ethyl alcohol is only a considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Ethyl alcohol	64-17-5	Developmental	-	Developmental Carcinogen
State Right-to-Know				

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ethyl alcohol	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class

B2 Flammable liquid

D2A Very toxic materials

D2B Toxic materials



16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 24-Apr-2009

 Revision Date
 19-May-2015

 Print Date
 19-May-2015

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS); SDS sections

updated; 2

Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of SDS