

SAFETY DATA SHEET

Creation Date 29-Jun-2009 Revision Date 12-May-2014 Revision Number 1

1. Identification

Product Name sec-Butanol

Cat No.: AC107700000; AC107700010; AC107700025; AC107700100

Synonyms sec-Butyl alcohol, 2-Butanol

Recommended Use Laboratory chemicals.

Uses advised against No Information available

Details of the supplier of the safety data sheet

Company Entity / Business Name

Fisher Scientific Acros Organics
One Reagent Lane One Reagent Lane
Fair Lawn, NJ 07410 Fair Lawn, NJ 07410

Fair Lawn, NJ 07410 Tel: (201) 796-7100 **Emergency Telephone Number**

For information US call: 001-800-ACROS-01

/ Europe call: +32 14 57 52 11

Emergency Number **US:**001-201-796-7100 /

Europe: +32 14 57 52 99

CHEMTREC Tel. No.US:001-800-424-9300 /

Europe:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids
Serious Eye Damage/Eye Irritation
Specific target organ toxicity (single exposure)

Category 3
Category 3

Target Organs - Respiratory system, Central nervous system (CNS).

Label Elements

Signal Word

Warning

Hazard Statements

Flammable liquid and vapor Causes serious eye irritation May cause respiratory irritation May cause drowsiness or dizziness

sec-Butanol Revision Date 12-May-2014



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Skir

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None identified

3. Composition / information on ingredients

Component	CAS-No	Weight %	
sec-Butyl alcohol	78-92-2	>95	

4. First-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Obtain medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if

symptoms occur.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Obtain medical attention.

Ingestion Do not induce vomiting. Obtain medical attention.

Most important symptoms/effects Breathing difficulties. Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed

containers exposed to fire with water spray.

Unsuitable Extinguishing Media No information available

Flash Point 24 °C / 75.2 °F

Method - No information available

Autoignition Temperature 390 °C / 734 °F

Explosion Limits

 Upper
 9.8% @ 100°C

 Lower
 1.7% @ 100°C

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO2) peroxides

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
2	3	0	N/A

6. Accidental release measures

Personal Precautions Use personal protective equipment. Remove all sources of ignition. Take precautionary

measures against static discharges.

Environmental Precautions Avoid release to the environment. See Section 12 for additional ecological Information.

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, **Up** closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

7	 land	lina	and	stor	ODE
/ /	 ıaııu	HII	anu	StOI	auc

Handling Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Avoid

ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use explosion-proof equipment. Take precautionary measures

against static discharges.

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area.

Keep away from heat and sources of ignition. May form explosive peroxides on prolonged

storage.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
sec-Butyl alcohol	TWA: 100 ppm	(Vacated) TWA: 100 ppm	IDLH: 2000 ppm
		(Vacated) TWA: 305 mg/m ³	TWA: 100 ppm
		TWA: 150 ppm	TWA: 305 mg/m ³
		TWA: 450 mg/m ³	STEL: 150 ppm
			STEL: 455 mg/m ³
Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV

sec-Butyl alcohol	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm
78-92-2 (>95)	TWA: 303 mg/m ³	TWA: 305 mg/m ³	
	_	STEL: 150 ppm	
		STEL: 455 mg/m ³	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures Ensure that eyewash stations and safety showers are close to the workstation location.

Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Eye/face ProtectionWear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protectionWear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorsweet

Odor Threshold No information available pH No information available

Melting Point/Range -115 °C / -175 °F

Boiling Point/Range 99 °C / 210.2 °F @ 760 mmHg

Flash Point 24 °C / 75.2 °F
Evaporation Rate No information available
Flammability (solid,gas) No information available

Flammability or explosive limits

 Upper
 9.8% @ 100°C

 Lower
 1.7% @ 100°C

 Vapor Pressure
 17 mbar @ 20 °C

 Vapor Density
 2.6 (Air = 1.0)

 Relative Density
 0.800

Solubility < 12.5 g/1000 ml @ 20 °C

Partition coefficient; n-octanol/water

Autoignition Temperature

Decomposition temperature

Viscosity

No data available
390 °C / 734 °F
No information available
4.2 mPa.s @ 20 °C

Molecular Formula C4 H10 O Molecular Weight 74.12

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions. May form explosive peroxides on prolonged storage.

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition. Incompatible products.

Exposure to light. Exposure to air.

Incompatible Materials Strong oxidizing agents, Acid chlorides, Acid anhydrides

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), peroxides

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Component Information

Component LD50 Oral		LD50 Dermal	LC50 Inhalation	
sec-Butyl alcohol	2193 mg/kg (Rat)	2 g/kg (Rat)	48500 mg/m³ (Rat) 4 h	

Toxicologically Synergistic

No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes and respiratory system

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
sec-Butyl alcohol	78-92-2	Not listed				

Mutagenic Effects Not mutagenic in AMES Test

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Respiratory system Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects See actual entry in RTECS for complete information.

12. Ecological information

Ecotoxicity

.

	Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
ſ	sec-Butyl alcohol	Not listed	Pimephales promelas: LC50:	Pseudomonas putida: 500	EC50: 3750 mg/L/24h
l	•		3670 mg/L/96h	mg/L/16h	

Persistence and Degradability

No information available

Bioaccumulation/ Accumulation No information available.

Mobility

Component	log Pow
sec-Butyl alcohol	0.6

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Revision Date 12-May-2014

sec-Butanol

DOT

UN-No UN1120
Proper Shipping Name BUTANOLS

Hazard Class 3
Packing Group III

TDG

UN-No UN1120 Proper Shipping Name BUTANOLS

Hazard Class 3
Packing Group III

IATA

UN-No UN1120
Proper Shipping Name Butanols
Hazard Class 3
Packing Group III

IMDG/IMO

UN-No UN1120
Proper Shipping Name Butanols
Hazard Class 3
Packing Group III

15. Regulatory information

14. Transport information

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
sec-Butyl alcohol	Х	Х	-	201-158-5	-		Χ	Χ	Х	Х	Х

Legend:

- X Listed
- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
sec-Butyl alcohol	78-92-2	>95	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard Yes
Chronic Health Hazard No
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

Clean Water Act Not applicable

Clean Air Act Not applicable

sec-Butanol Revision Date 12-May-2014

OSHA Occupational Safety and Health Administration

Not applicable

CERCLA

Not applicable

California Proposition 65

This product does not contain any Proposition 65 chemicals

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
sec-Butyl alcohol	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class

B2 Flammable liquid
D2B Toxic materials



16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 29-Jun-2009

 Revision Date
 12-May-2014

 Print Date
 12-May-2014

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS)

Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of SDS