Reviewed On: 04/22/2016



Safety Data Sheet acc. to OSHA HCS

Date Prepared: 06/03/2016

1 Identification

· Product Identifier:

- · Product Name: Sedi-Stain
- · Catalog Number: 421571
- · Application of the substance / the mixture Laboratory Chemicals
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: BD Diagnostic Systems
 7 Loveton Circle
 Sparks, MD 21152
 Telephone: (410) 771 - 0100 or (800) 638 – 8663
 Email Address: Technical_Services@bd.com
 Information Department: Technical Service
- Emergency telephone number: In case of a chemical emergency, spill, fire, exposure, or accident, contact BD Diagnostic Systems (410) 771-0100 or (800)-638-8663, or ChemTrec at (800) 424-9300.

2 Hazard(s) identification

· Classification of the substance or mixture



Flam. Liq. 3 H226 Flammable liquid and vapor.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



- · Signal word Warning
- Hazard-determining components of labeling: ethanol
 C.I. Basic Violet 3
- · Hazard statements
- H226 Flammable liquid and vapor.
- · Precautionary statements
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P240 Ground/bond container and receiving equipment.

(Contd. on page 2)



Date Prepared: 06/03/2016

Reviewed On: 04/22/2016

Product Name: Sedi-Stain

(Contd. of page 1)				
Keep container tightly closed.				
Use only non-sparking tools.				
Take precautionary measures against static discharge.				
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.				
In case of fire: Use for extinction: CO2, powder or water spray.				
Store in a well-ventilated place. Keep cool.				
Dispose of contents/container in accordance with local/regional/national/ international regulations.				
· NFPA ratings (scale 0-4)				
= 0 ability = 2 vity = 0				

· HMIS ratings (scale 0-4)

HEALTHImage: OFIREImage: OFIREImage: OREACTIVITYImage: OReactivityImage: O

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixture

· Description: Mixture consisting of the following components.

· Dangerous Components:				
CAS: 64-17-5	ethanol	10.0%		
EINECS: 200-578-6	Flam. Liq. 2, H225			
	C.I. Basic Violet 3	0.1%		
EINECS: 208-953-6	Carc. 2, H351; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302			
Additional information Risk phrases refer to section 15				

Additional information Risk phrases refer to section 15.

4 First-aid measures

· Description of first aid measures

- · General information No special measures required.
- After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

US



Date Prepared: 06/03/2016

Reviewed On: 04/22/2016

Product Name: Sedi-Stain

(Contd. of page 2)

• After eye contact Rinse opened eye for 15 minutes under running water. Then consult a doctor.

- After swallowing Immediately call a doctor.
- · Information for doctor Show this product label or this SDS.
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents CO2, ABC multipurpose dry chemical or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Wipe up with damp sponge or mop.
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders). Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- · Handling
- · Precautions for safe handling No special measures required.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 4)

US



Date Prepared: 06/03/2016

Reviewed On: 04/22/2016

Product Name: Sedi-Stain

(Contd. of page 3)

- Information about storage in one common storage facility: Store away from oxidizing agents.
- Further information about storage conditions: Store in cool, dry conditions in well sealed containers.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see Section 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

64-17-5 ethanol

PEL 1900 mg/m³, 1000 ppm

- REL 1900 mg/m³, 1000 ppm
- TLV 1880 mg/m³, 1000 ppm

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal Protective Equipment
- General protective and hygienic measures Wash hands before breaks and at the end of work.
- **Breathing equipment:** In case of brief exposure, use a chemical fume hood or a NIOSH/MSHA-approved respirator.
- Protection of hands:



Chemical resistant gloves (i.e. nitrile, or equivalent).

· Eye protection:

- Safety glasses
- Tightly sealed goggles.
- · Body protection: Protective work clothing (lab coat).

9 Physical and chemical properties

- Information on basic physical and chemical properties
- · General Information
- · Appearance:
 - Form: Color:

Liquid Purple

(Contd. on page 5)

US



Date Prepared: 06/03/2016

Reviewed On: 04/22/2016

Product Name: Sedi-Stain

	(Contd. of page
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	6.0 +/- 0.1
Change in condition	
Melting point/Melting range:	Not determined
Boiling point/Boiling range:	Not determined
Flash point:	52.2 °C (126 °F)
Flammability (solid, gaseous)	Not applicable.
Ignition temperature:	425.0 °C (797 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self igniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	3.5 Vol %
Upper:	15.0 Vol %
Density:	Not determined
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Soluble
Partition coefficient (n-octanol/wa	ter): Not determined.
Viscosity:	
dynamic:	Not determined.
kinematic:	Not determined.
Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Incompatible material: strong oxidizers.

(Contd. on page 6)



Date Prepared: 06/03/2016

Reviewed On: 04/22/2016

Product Name: Sedi-Stain

(Contd. of page 5)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:
 - 64-17-5 ethanol

Oral LD50 3450 mg/kg (MOU)

7060 mg/kg (rat)

- Primary irritant effect:
- · on the skin: No irritating effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Subacute to chronic toxicity: Target organs: thyroid, kidney, ureter or bladder tumors.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- Other information:

The ecological effects have not been thoroughly investigated, but currently none have been identified.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 7)

(Contd. of page 6)

🍪 BD

Safety Data Sheet acc. to OSHA HCS

Date Prepared: 06/03/2016

Product Name: Sedi-Stain

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

RCRA hazardous waste - RCRA # D001 (ignitable). Must not be disposed of with solid waste. Dispose of material in accordance with federal (40 CFR 261.3), state and local requirements.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to state and federal regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number	
· DOT, ADN, IMDG, IATA	Void
· UN proper shipping name	
· DOT, ADN, IMDG, IATA	Void
· Transport hazard class(es)	
· DOT, ADN, IMDG, IATA	
· Class	Void
· Packing group	
· DOT, IMDG, IATA	Void
· Environmental hazards:	
• Marine pollutant:	No
 Special precautions for user 	Not applicable.
· Transport in bulk according to Annex II o	
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
·DOT	
· Remarks:	49CFR 173.150(e)(2) - States that aqueous solution of alcohol containing 24 percent or less alcohol by volume and no other hazardous
	(Contd. on page 8



Date Prepared: 06/03/2016

Reviewed On: 04/22/2016

Product Name: Sedi-Stain

	(Contd. of page 7
	material can be re-class as a combustible liquid and is not subject to the requirements.
· IMDG · Remarks:	IMDG Special Provision 144 - An aqueous solution containing not more than 24% alcohol by volume is not subject to the provisions of this code.
· IATA · Remarks:	IATA Special Provision A58 - Aqueous solutions containing 24% or less alcohol by volume is not subject to these regulations.
· UN "Model Regulation":	Void

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · SARA Section 355 (extremely hazardous substances)
- None of the ingredients is listed.
- · SARA Section 313 (specific toxic chemical listings)
- 64-17-5 ethanol
- · TSCA (Toxic Substances Control Act)
 - 7732-18-5 water
 - 64-17-5 ethanol
 - 477-73-6 safranin o
 - 548-62-9 C.I. Basic Violet 3
- · California Proposition 65 Chemicals known to cause cancer
- None of the ingredients is listed.
- California Proposition 65 Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

 California Proposition 65 - Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed.

· California Proposition 65 - Chemicals known to cause developmental toxicity:

64-17-5 ethanol

(Contd. on page 9)

Reviewed On: 04/22/2016



Safety Data Sheet acc. to OSHA HCS

Date Prepared: 06/03/2016

Product Name: Sedi-Stain

Carcinogenic ca TLV (Threshold 64-17-5 ethanol	ntegories Limit Value established by ACGIH)
•	Limit Value established by ACGIH)
64-17-5 ethanol	
• GHS label elem The product is cl • Hazard pictogra	assified and labeled according to the Globally Harmonized System (GHS
GHS02	
· Signal word Wa	rning
ethanol C.I. Basic Violet • Hazard stateme H226 Flammable • Precautionary s	nts liquid and vapor.
P210 P241 P280 P240 P233	Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment. Wear protective gloves/protective clothing/eye protection/face protection Ground/bond container and receiving equipment. Keep container tightly closed.
P242 P243 P303+P361+P35	Use only non-sparking tools. Take precautionary measures against static discharge. 33 If on skin (or hair): Take off immediately all contaminated clothing. Rin skin with water/shower.
P370+P378 P403+P235 P501	In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/nation international regulations. assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

To the best of our knowledge, the information contained herein is accurate. However, neither Becton, Dickinson and Company or any of its subsidiaries assumes any liabilities whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we can not guarantee that these are the only hazards that exist.

(Contd. on page 10)

US



Date Prepared: 06/03/2016

Reviewed On: 04/22/2016

Product Name: Sedi-Stain

	(Contd. of page 9)
· Department issuing SDS:	
Environmental, Health & Safety	
Created by Michael J. Spinazzola	
• Contact: Technical Service Representative	
· Date of preparation / last revision 06/03/2016 / -	
• •	
Abbreviations and acronyms:	
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation IATA: International Air Transport Association	
ACGIH: American Conference of Governmental Industrial Hygienists	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative	
OSHA: Occupational Safety & Health	
TI V: Threshold I imit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
Flam. Liq. 2: Flammable liquids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Carc. 2: Carcinogenicity – Category 2	
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Categor	v 1
	y I