



SAFETY DATA SHEET

Revision Date 15-Jan-2021

Version 9

1. IDENTIFICATION

Product identifier

Product Name COPPER ANTI-SEIZE LUBRICANT 8OZ

Other means of identification

Product Code 09128

Recommended use of the chemical and restrictions on use

Recommended Use Lubricant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex
6875 Parkland Blvd.
Solon, Ohio 44139 USA
Telephone: 1-87-Permatex
(866) 732-9502

24-hour emergency phone number

Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

May Also Be Distributed by:

ITW Permatex Canada
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5
Telephone: (800) 924-6994

E-mail address: mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity	Category 1B
-----------------	-------------

Label elements

Emergency Overview

Signal word

Danger

May cause cancer



Appearance Copper	Physical state Paste Liquid	Odor Petroleum
--------------------------	------------------------------------	-----------------------

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN: Gently wash with plenty of soap and water
If skin irritation occurs: Get medical advice/attention

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Very toxic to aquatic life with long lasting effects.

Unknown acute toxicity 27.25 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

The product contains no substances which at their given concentration, are considered to be hazardous to health.

Chemical Name	CAS No	Weight-%
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	30 - 60
MAGNESIUM SILICATE	14807-96-6	10 - 30
LIMESTONE	1317-65-3	10 - 30
COPPER	7440-50-8	3 - 7
GRAPHITE	7782-42-5	1 - 5
AMORPHOUS SILICA	7631-86-9	1 - 5

4. FIRST AID MEASURES

Description of first aid measures

General advice	Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.
Eye contact	In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
Skin contact	IF ON SKIN: Wash with soap and water.
Inhalation	Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Administer oxygen if breathing is difficult.

Ingestion IF SWALLOWED: Do NOT induce vomiting.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO₂, water spray or regular foam, Water spray, fog or regular foam, Move containers from fire area if you can do it without risk, Dike fire-control water for later disposal

Unsuitable extinguishing media

Do not scatter spilled material with high pressure water streams

Specific hazards arising from the chemical

Some may burn but none ignite readily. Those substances designated with a "P" may polymerize explosively when heated or involved in a fire. Some may be transported hot.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Do not touch or walk through spilled material. Stop leak if you can do it without risk.

Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for containment Prevent dust cloud.

Methods for cleaning up Cover liquid spill with sand, earth or other non-combustible absorbent material. With clean shovel place material into clean, dry container and cover loosely; move containers from spill area. Take up with sand or other non-combustible absorbent material and place into containers for later disposal. Cover powder spill with plastic sheet or tarp to minimize spreading.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with skin and eyes.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep in a dry, cool and well-ventilated place.

Incompatible materials Strong oxidizing agents, Acids, Alkalis

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
MAGNESIUM SILICATE 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	(vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more; use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
LIMESTONE 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
COPPER 7440-50-8	TWA: 0.2 mg/m ³ fume	TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ dust and mist (vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume
GRAPHITE 7782-42-5	TWA: 2 mg/m ³ respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ natural respirable dust
AMORPHOUS SILICA 7631-86-9	-	TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 6 mg/m ³ <1% Crystalline silica TWA: 20 mppcf : (80)/(% SiO ₂) mg/m ³ TWA	IDLH: 3000 mg/m ³ TWA: 6 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	Paste Liquid
Appearance	Copper
Odor	Petroleum
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	No information available	
Flash point	216 °C / 421 °F	
Evaporation rate	No information available	Butyl acetate = 1
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	Air = 1
Relative density	1.21	
Water solubility	Insoluble in water	
Solubility(ies)	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC content	0%
Density	No information available
Bulk density	No information available
SADT (self-accelerating decomposition temperature)	No information available

10. STABILITY AND REACTIVITY

Reactivity

No information available

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents, Acids, Alkalis

Hazardous Decomposition Products

Carbon oxides

Metal oxides

Halogenated compounds

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation	May cause irritation of respiratory tract.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis.
Ingestion	Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC 64742-54-7	> 15 g/kg (Rat)	> 5000 mg/kg (Rabbit)	-
GRAPHITE 7782-42-5	-	-	> 2000 mg/m ³ (Rat) 4 h
AMORPHOUS SILICA 7631-86-9	= 7900 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 2.2 mg/L (Rat) 1 h

Information on toxicological effects**Symptoms** No information available.**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Sensitization** No information available.**Germ cell mutagenicity** No information available.**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC 64742-54-7	A2	Group 1	Known	X
MAGNESIUM SILICATE 14807-96-6	-	Group 3	-	X
AMORPHOUS SILICA 7631-86-9	-	Group 3	-	-

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - *Suspected Human Carcinogen*

IARC (International Agency for Research on Cancer)

Group 1 - *Carcinogenic to Humans**Not classifiable as a human carcinogen*

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - *Present***Chronic toxicity** May cause adverse liver effects.**Target Organ Effects** Central Vascular System (CVS), Eyes, kidney, Liver, Respiratory system, Skin.**The following values are calculated based on chapter 3.1 of the GHS document .****ATEmix (oral)** 18281 mg/kg**ATEmix (dermal)** 6332 mg/kg

12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a severe marine pollutant according to DOT.

Ecotoxicity

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.
US EPA Waste Number	Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. TRANSPORT INFORMATION

DOT

Proper shipping name	Not regulated
Marine pollutant	This product contains a chemical which is listed as a severe marine pollutant according to DOT.

IATA

Proper shipping name	Not regulated
-----------------------------	---------------

IMDG

Proper shipping name	Not regulated
-----------------------------	---------------

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Does not comply
IECSC	Complies
KECL	Complies
PICCS	Complies

AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
COPPER - 7440-50-8	1.0

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
COPPER 7440-50-8	-	X	X	-

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
COPPER 7440-50-8	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
AMORPHOUS SILICA 7631-86-9	*Carcinogen

*The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
MAGNESIUM SILICATE 14807-96-6	X	X	X
LIMESTONE 1317-65-3	X	X	X
COPPER 7440-50-8	X	X	X
AMORPHOUS SILICA 7631-86-9	-	X	X
GRAPHITE 7782-42-5	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2A - Very toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 1	Flammability 1	Instability 0	-
HMIS	Health hazards 1	Flammability 1	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date 15-Jan-2021

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet